



## C16000385 - C16000386 - C16000387 Twin Thermostats

Characteristics	M.U.	TX-C16000385	TX-C16000386	TX-C16000387
Setting range	°C	0 +60 / 0 +60	0 +60 / 0 +60	-10 +50 / +20 +80
Contact	-	NC/NO	NO/NO	NC/NO
Switch difference	K	7	7	7
Switching capacity (resistive load)	A	10	10	10
Max. tension	V	250 AC	250 AC	250 AC
Height	mm	67	67	67
Width	mm	50	50	50
Depth	mm	46	46	46
Sensor element	-	Bimetal	Bimetal	Bimetal
Electrical connection	-	4-pole terminal (2.5 mm <sup>2</sup> )	4-pole terminal (2.5 mm <sup>2</sup> )	4-pole terminal (2.5 mm <sup>2</sup> )
Operating temperature limits	°C	-20 +80	-20 +80	-20 +80
Protection level EN60529	-	IP20	IP20	IP20
Mounting on clip for DIN bar	mm	35	35	35
Weight	g	30	30	30
Conformity	-	CE ; UL	CE ; UL	CE ; UL



### Accessories / Options

Pack of 5 devices installation accessories for electrical enclosures

AAWTC10

Wiring Diagram

