



- Suitable for the mounting of supply authority and private current transformers.
- Manufactured from 1.6mm zinc coated steel or 316 stainless steel available on request.
- Powdercoated Pebble Grey RAL7032.
- AS/NZS 61439 compliant documentation provided.



SMB1/15

ORDERING GUIDE

				Dimensions (mm)		
Part Number	Description	Switchboard Max Rating	Type Test Certification	Height	Width	Depth
SMB ENCLOSURES IP66						
SMB1/15	Cabinet supplied with meter and consumer panel (ex VIC)	490A	36kA for 1 sec	2075	800	500
SMB1/15/S	Cabinet supplied with meter and consumer panel (ex VIC)	490A	36kA for 1 sec	2075	800	500
CT ENCLOSURES IP23						
CTB/E2	Enclosure is weather proof to IP23 and includes potential fuse holders and 32A fuse cartridges. Excludes CT chassis to be ordered separately. Suitable for either CTC200/400A or CTC630A. Painted RAL7035 Light Grey.			500	720	340
CT CHASSIS						
CTC200/400A^	CT chassis for S-Type CTs	200/400A	25kA for 1 sec	500	400	95
CTC630A^	CT chassis for T-Type CTs	630A	36kA for 1 sec	500	400	120

^ Type test certificates available on request.

ACCESSORIES

Part Number	Description	CTB/E2
CTPFK	Potential fuse kit with cover for sealing and insulating base-plate (excludes fuses).	•
LKDCT10016	QLD Meter Isolation Link, with link, clear	
LKDVA10000	Authority CT Metering Block, with Z links	
LKDVA10001	Authority CT 200/5 Extended Range, S-type, each	
LKDVA10002	Authority CT 800/5 Extended Range, T-type, set of 3	
LKDVF10000^	NSW fuse holder only, 30.2x58mm, w. Barrier	
LKDVF10002	Standard 100A fuse holder only, 22x58mm, clear	

▲ Available on request.



CTPFK



CTB/E2