

Horizon N Series  
Residential metering enclosures for NSW applications



- Designed for both single and multi-phase installations.
- AS/NZS3012 compliant for construction sites as standard.
- Region D wind rated to AS1170.2-2002: Structural design actions – Wind actions.
- Provide safety, quality and performance.
- Suitable for domestic and light commercial metering applications.
- Self-closing gravity catch.
- Top cable entry has ratchet aperture shut-off slide.
- RotaDIN® rotating / removable DIN section.
- Cord retainer for easy retention of extension cords.
- Circuit identification label area with protective cover.
- Weatherproof installation label for AS/NZS3000 compliance.
- Padlockable facility.
- External frame mounting brackets.
- Manufactured from 1.0 galvanised steel or 316 stainless steel.
- Powdercoated Light Grey RAL7035 or N4.



N20

ORDERING GUIDE

| Part Number        | DIN space | Dimensions (mm)      |        |       |       | Panel (mm) |       |              |
|--------------------|-----------|----------------------|--------|-------|-------|------------|-------|--------------|
|                    |           | Earth & Neutral Link | Height | Width | Depth | Height     | Width | Depth Behind |
| N20*               | 24-pole   | E9P, N18P + stud     | 690    | 485   | 278   | 480        | 461   | 75           |
| N20/S <sup>i</sup> | 24-pole   | E9P, N18P + stud     | 690    | 485   | 278   | 480        | 461   | 75           |
| N22*               | 48-pole   | E9P, N18P + stud     | 860    | 485   | 278   | 480        | 461   | 75           |

<sup>i</sup> Available on request.  
\* Comes with pre-drilled panel for single or 3Ø metering

ACCESSORIES

| Part Number   | Product                              | Description                                                                                                                                       | N20 | N20/S | N22 |
|---------------|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|-----|-------|-----|
| HZN/ROOF      | Roof - Galvanised Steel<br>RAL7035   | For use in exposed weather conditions                                                                                                             | •   |       | •   |
| HZN/ROOF/S▲   | Roof - Stainless Steel               |                                                                                                                                                   |     | •     |     |
| HZN/PLINTH    | Plinth - Galvanised Steel<br>RAL7035 | Designed to mate under a standard meter box.<br>Plinth dimension: 690Hx485Wx240D<br>Compliant to region C wind load according to AS/<br>NZS1170.2 | •   |       | •   |
| HZN/PLINTH/S▲ | Plinth - Stainless Steel             |                                                                                                                                                   |     | •     |     |
| HZN/FK8       | Flush Kit                            | Flush kit                                                                                                                                         | •   |       |     |


▲ Available on request.



N20/S



HZN/PLINTH



HZN/ROOF