

Monarch IP Viewing Window - Zinc Coated Steel

Industrial Enclosure & Switchboard Building System



- Suitable for small motor control applications, lighting, CT metering and smaller switchboard applications.
- Premium enclosure and switchboard building system designed to be the ultimate in flexibility.
- Conformity, Approvals:
 - Lloyds Register #06/10007 (E2)
- Region D wind rated to AS1170.2-2002: Structural design actions - Wind actions
- Manufactured from 1.2/1.5mm 316 stainless steel.
- N4 surface finish or Powdercoated X15 Orange.

Comes standard with:

- 'C' rail mountings (4 rails on heights up to 800mm and 8 rails on 1200mm and above)
- Gland plate (fitted internally or externally on 400mm deep and deeper)
- Stainless steel lock with 7mm square stainless steel insert (IP020/S) on units below 1600mm high and lockable L handles (IP050) on others
- 3-point locking on units of 600mm high and above
- Removable back on units 400mm deep and deeper
- Door rails and earth strap kit
- Laminated glass viewing window - 5.4mm thick



ACCESSORIES QUICK SELECTION

Accessories	Page No.	Accessories	Page No.	Accessories	Page No.
Rainhoods	3	Escutcheon Rails	9	19" Mounting Rails	11
Gland Plates	3	Universal Rail Kits	9	Laptop Lectors	12
Plinths	4	Door Stays	9	Document Holders	12
Vent Kits	4	Shelves	10	Schedule Holders	12
Vent Hoods	5	DIN Rails	10	Backmount Frame	12
Mounting Pans	5	Eye Bolts	10	Load Centre	12
Insulated Mounting Panels	6	Mounting Brackets	10	General Accessories	13
Double Hinged Insulating Panels	6	Standard Rails – C Section	11	Locks	14
Hinged & Fixed Escutcheons	7-8	Universal Rails	11	Lighting	15

Monarch IP Viewing Window - Zinc Coated Steel

Industrial Enclosure & Switchboard Building System

ORDERING GUIDE

		Dimensions (mm)							Viewing Window			Weight (kg)
		External			Gland Opening		Opening					
Part Number	Part Number X15 Ripple Orange	Height (A)	Width (B)	Depth (C)	Width (D)	Depth (E)	Height (F)	Width (G)	Height (H)	Width (I)	Weight (kg)	
IP13132/S/WG▲	IP13132/SRO/WG▲	400	400	270	—	—	340	340	185	185	16.0	
IP21132/S/WG▲	IP21132/SRO/WG▲	600	400	270	—	—	540	340	375	170	16.0	
IP13212/S/WG▲	IP13212/SRO/WG▲	400	600	270	—	—	340	540	175	370	16.0	
IP21212/S/WG▲	IP21212/SRO/WG▲	600	600	270	—	—	540	540	375	370	21.0	
IP29212/S/WG▲	IP29212/SRO/WG▲	800	600	270	—	—	740	540	575	370	26.0	
IP37212/S/WG▲	IP37212/SRO/WG▲	1000	600	270	—	—	940	540	775	370	31.0	
IP45212/S/WG▲	IP45212/SRO/WG▲	1200	600	270	—	—	1140	540	975	370	36.0	
IP21292/S/WG▲	IP21292/SRO/WG▲	600	800	270	—	—	540	740	375	570	26.0	
IP13214/S/WG▲	IP13214/SRO/WG▲	400	600	400	490	170	340	540	175	370	20.0	
IP21214/S/WG▲	IP21214/SRO/WG▲	600	600	400	490	170	540	540	375	370	25.0	
IP29214/S/WG▲	IP29214/SRO/WG▲	800	600	400	490	170	740	540	575	370	31.0	
IP45214/S/WG▲	IP45214/SRO/WG▲	1200	600	400	490	170	1140	540	975	370	42.0	
IP61214/S/WG▲	IP61214/SRO/WG▲	1600	600	400	490	170	1540	540	1375	370	53.0	
IP69214/S/WG▲	IP69214/SRO/WG▲	1800	600	400	490	170	1740	540	1575	370	59.0	
IP77214/S/WG▲	IP77214/SRO/WG▲	2000	600	400	490	170	1940	540	1775	370	65.0	
IP25254/S/WG▲	IP25254/SRO/WG▲	700	700	400	490	170	640	640	475	470	71.0	
IP37254/S/WG▲	IP37254/SRO/WG▲	1000	700	400	490	170	940	640	775	470	31.0	
IP21294/S/WG▲	IP21294/SRO/WG▲	600	800	400	490	170	540	740	375	570	40.0	
IP29294/S/WG▲	IP29294/SRO/WG▲	800	800	400	490	170	740	740	575	570	31.0	
IP37294/S/WG▲	IP37294/SRO/WG▲	1000	800	400	490	170	940	740	775	570	38.0	
IP45294/S/WG▲	IP45294/SRO/WG▲	1200	800	400	490	170	1140	740	975	570	44.0	
IP61294/S/WG▲	IP61294/SRO/WG▲	1600	800	400	490	170	1540	740	1375	570	51.0	
IP69294/S/WG▲	IP69294/SRO/WG▲	1800	800	400	490	170	1740	740	1575	570	64.0	
IP77294/S/WG▲	IP77294/SRO/WG▲	2000	800	400	490	170	1940	740	1775	570	71.0	
IP77135/S/WG▲	IP77135/SRO/WG▲	2000	800	400	490	170	1940	740	1775	170	78.0	
IP21295/S/WG▲	IP21295/SRO/WG▲	600	800	500	490	170	540	740	575	370	35.0	
IP29215/S/WG▲	IP29215/SRO/WG▲	800	600	500	490	170	740	540	975	370	35.0	
IP45215/S/WG▲	IP45215/SRO/WG▲	1200	600	500	490	170	1140	540	1375	370	47.0	
IP61215/S/WG▲	IP61215/SRO/WG▲	1600	600	500	490	170	1540	540	1575	370	60.0	
IP69215/S/WG▲	IP69215/SRO/WG▲	1800	600	500	490	170	1740	540	1775	370	66.0	
IP77215/S/WG▲	IP77215/SRO/WG▲	2000	600	500	490	170	1940	540	375	570	72.0	
IP45295/S/WG▲	IP45295/SRO/WG▲	1200	800	500	490	170	1140	740	975	570	57.0	
IP61295/S/WG▲	IP61295/SRO/WG▲	1600	800	500	490	170	1540	740	1375	570	71.0	
IP69295/S/WG▲	IP69295/SRO/WG▲	1800	800	500	490	170	1740	740	1575	570	78.0	
IP77295/S/WG▲	IP77295/SRO/WG▲	2000	800	500	490	170	1940	740	1775	570	85.0	
IP77136/S/WG▲	IP77136/SRO/WG▲	2000	400	600	120	440	1940	340	1775	170	73.0	
IP29216/S/WG▲	IP29216/SRO/WG▲	800	600	600	490	170	740	540	575	370	39.0	
IP45216/S/WG▲	IP45216/SRO/WG▲	1200	600	600	490	170	1140	540	975	370	52.0	
IP61216/S/WG▲	IP61216/SRO/WG▲	1600	600	600	490	170	1540	540	1375	370	66.0	
IP77216/S/WG▲	IP77216/SRO/WG▲	2000	600	600	490	170	1940	540	1775	370	79.0	
IP77296/S/WG▲	IP77296/SRO/WG▲	2000	800	600	490	170	1940	740	1775	570	93.0	
IP77218/S/WG▲	IP77218/SRO/WG▲	2000	600	800	490	170	1940	540	1775	370	99.6	
IP77298/S/WG▲	IP77298/SRO/WG▲	2000	800	800	490	170	1940	740	1775	570	116.5	

▲ Available on request

Monarch IP

Accessories to suit all Monarch IP enclosures



Rainhoods


Rainhoods are designed to shed water from the top of the enclosure to prevent it from pooling on top of the enclosure. The rainhoods have an overhang of 14mm.

Part Number	Material	Dimensions (mm)			Slope Angle (Degrees)	To suit enclosures (mm)	
		Height	Width	Depth		Width	Depth
IPRH132▲	Zinc coated steel	30	400	284	2.0	400	270
IPRH211▲		30	600	189	3.0	600	175
IPRH212		30	600	284	2.0	600	270
IPRH214		30	600	414	1.5	600	400
IPRH215▲		30	600	514	1.0	600	500
IPRH216▲		30	600	614	1.0	600	600
IPRH254		30	700	414	1.5	700	400
IPRH292▲		30	800	284	2.0	800	270
IPRH294		30	800	414	1.5	800	400
IPRH295		30	800	514	1.0	800	500
IPRH296▲		30	800	614	1.0	800	600
IPRH051/S▲	316 stainless steel	30	200	189	3.0	200	175
IPRH091/S▲		30	300	189	3.0	300	175
IPRH132/S		30	400	284	2.0	400	270
IPRH211/S▲		30	600	189	3.0	600	175
IPRH212/S		30	600	284	2.0	600	270
IPRH214/S		30	600	414	1.5	600	400
IPRH215/S▲		30	600	514	1.0	600	500
IPRH216/S		30	600	614	1.0	600	600
IPRH254/S▲		30	700	414	1.5	700	400
IPRH292/S▲		30	800	284	2.0	800	270
IPRH294/S		30	800	414	1.5	800	400
IPRH295/S		30	800	514	1.0	800	500
IPRH296/S▲		30	800	614	1.0	800	600

▲ Available on request



Zinc coated steel rainhood on cabinet




Zinc coated steel rainhood

Gland Plates

Designed for efficient and flexible fitting and installation of cable glands.

Part Number	Material	Dimensions (mm)			To suit enclosure (mm)	
		Width	Depth	Thickness	Width	Depth
IPGP31▲	Zinc coated steel	290	160	1.6	400	270
IPGP41▲		480	160	1.6	600 or 800	270
IPGP52▲		530	210	1.6	600, 700 or 800	400, 500 or 600
IPGS31	316 stainless steel	290	160	1.5	400	270
IPGS41		480	160	1.5	600 or 800	270
IPGS52		530	210	1.5	600, 700 or 800	400, 500 or 600
IPGB31	Brass	290	160	6	400	270
IPGB41		480	160	6	600 or 800	270
IPGB52		530	210	6	600, 700 or 800	400, 500 or 600
IPGA31	Aluminium	290	160	2.5	400	270
IPGA41		480	160	2.5	600 or 800	270
IPGA52		530	210	2.5	600, 700 or 800	400, 500 or 600

▲ Available on request



IPGP

Monarch IP

Accessories to suit all Monarch IP enclosures

Plinths

Designed for use when mounting enclosures on the floor.

Product	Material	Part Number	Dimensions (mm)			To suit enclosures (mm)	
			Height	Width	Depth	Width	Depth
Access plinths	Steel	IPPH214	200	600	374	600	400
		IPPH215▲	200	600	474	600	500
		IPPH216▲	200	600	574	600	600
		IPPH294	200	800	374	800	400
		IPPH295	200	800	474	800	500
		IPPH296▲	200	800	574	800	600
	316 stainless steel	IPPH295/3▲	300	800	470	800	500
		IPPH214/S	200	600	374	600	400
		IPPH215/S▲	200	600	474	600	500
		IPPH216/S▲	200	600	574	600	600
		IPPH294/S	200	800	374	800	400
		IPPH295/S	200	800	474	800	500
Plinth	Channel iron	IPPH296/S▲	200	800	574	800	600
		IPPC212	75	600	241	600	270
		IPPC214	75	600	371	600	400
		IPPC215	75	600	471	600	500
		IPPC216	75	600	571	600	600
		IPPC254	75	700	371	700	400
		IPPC294	75	800	371	800	400
		IPPC295	75	800	471	800	500
		IPPC296▲	75	800	571	800	600
		IPPC424	75	1200	371	1200	400
		IPPC425▲	75	1200	471	1200	500
		IPPC504	75	1400	371	1400	400
		IPPC505▲	75	1400	471	1400	500
		IPPC584	75	1600	371	1600	400
		IPPC585	75	1600	471	1600	500
Clamp bracket	Set of 4 (for use with channel iron plinth)	IPPCB	–	–	–	all	all
Gasket	Neoprene (4m length)	IPPC/G	3	20	–	all	all



IPPC

▲ Available on request

Vent Kits – IP23

Ensure that the enclosure does not become excessively hot by allowing natural circulation of air.

The vent kit includes a gasket, insert filter and fittings. Note that by the nature of this item, the enclosure will then not be rated to IP66.

Part Number	Material	Description	Dimensions (mm)		
			Height	Width	To suit cutout (mm)
IPVK	Zinc coated steel	Powdercoated RAL7032	130	130	80 x 80
IPVK/LG		Powdercoated RAL7035	130	130	80 x 80
IPVK/RO		Powdercoated X15 Orange	130	130	80 x 80
IPVK16		Powdercoated RAL7032	260	260	190 x 190
IPVK16/LG▲		Powdercoated RAL7035	260	260	190 x 190
IPVK16/RO▲		Powdercoated X15 Orange	260	260	190 x 190
IPVK/S	316 stainless steel	–	130	130	80 x 80
IPVK/SRO▲		Powdercoated X15 Orange	130	130	80 x 80
IPVK16/S▲		–	260	260	190 x 190
IPVK16/SRO▲		Powdercoated X15 Orange	260	260	190 x 190
IPVK/A	Aluminium	Powdercoated RAL7035	130	130	80 x 80
IPVK16/A▲			260	260	190 x 190



IPVK

▲ Available on request

Monarch IP

Accessories to suit all Monarch IP enclosures



Vent Hoods

Designed to suit B&R's range of fans, filters and vent kits (on selected sizes) to ensure that the fan is protected mechanically and to protect from water and dust ingress.

Part Number	Material	Colour	Dimensions (mm)			To suit
			Height	Width	Depth	
IPVH12	Zinc coated steel	Pebble Grey RAL7032	300	200	50	FAN/FIL12 & IPVK
IPVH12/LG▲		Light Grey RAL7035	300	200	50	FAN/FIL12 & IPVK
IPVH12/RO		X15 Orange	300	200	50	FAN/FIL12 & IPVK
IPVH25		Pebble Grey RAL7032	400	300	50	FAN23/28 & FAN/FIL25
IPVH25/LG▲		Light Grey RAL7035	400	300	50	FAN23/28 & FAN/FIL25
IPVH25/RO		X15 Orange	400	300	50	FAN23/28 & FAN/FIL25
IPVH35		Pebble Grey RAL7032	475	375	75	FAN/FIL35
IPVH35/LG▲		Light Grey RAL7035	475	375	75	FAN/FIL35
IPVH35/RO▲		X15 Orange	475	375	75	FAN/FIL35
IPVH12/S	316 stainless steel	N4 finish	300	200	50	FAN/FIL12 & IPVK/S
IPVH12/SRO▲		X15 Orange	300	200	50	FAN/FIL12 & IPVK/S
IPVH25/S		N4 finish	400	300	50	FAN23/28 & FAN/FIL25
IPVH25/SRO		X15 Orange	400	300	50	FAN23/28 & FAN/FIL25
IPVH35/S		N4 finish	475	375	75	FAN/FIL35
IPVH35/SRO▲		X15 Orange	475	375	75	FAN/FIL35
IPVH12/A▲	Aluminium	Light Grey RAL7035	300	200	50	FAN/FIL12 & IPVK
IPVH25/A▲			400	300	50	FAN23/28 & FAN/FIL25
IPVH35/A▲			475	375	75	FAN/FIL35

▲ Available on request



IPVH on cabinet

Metal Mounting Pans

Very simple to install using the rails supplied as part of the Monarch IP enclosure. They are manufactured from 2mm thick pre-treated mild steel with a gloss white powdercoat finish.

Part Number	Dimensions (mm)			To suit enclosure (mm)	
	Height	Width	Thickness	Height	Width
IPMP0905	250	150	2	300	200
IPMP1309	350	250	2	400	300
IPMP1313	320	340	2	400	400
IPMP1321	320	540	2	400	600
IPMP2113	520	340	2	600	400
IPMP2121	520	540	2	600	600
IPMP2129	520	740	2	600	800
IPMP2525	620	640	2	700	700
IPMP2921#	720	540	2	800	600
IPMP2929#	720	740	2	800	800
IPMP3721#	920	540	2	1000	600
IPMP3725#	920	640	2	1000	700
IPMP3729#	920	740	2	1000	800
IPMP4521#	1120	540	2	1200	600
IPMP4529#	1120	740	2	1200	800
IPMP5321▲	1320	540	2	1400	600
IPMP5329▲	1320	740	2	1400	800
IPMP6121*	1520	540	2	1600	600
IPMP6129*	1520	740	2	1600	800
IPMP6921*	1720	540	2	1800	600
IPMP6929*	1720	740	2	1800	800
IPMP7721*	1920	540	2	2000	600
IPMP7729*	1920	740	2	2000	800

* Mounting pan features double return on sides and single return on top for extra rigidity.

Mounting pan features single return on sides.

▲ Available on request.



IPMP detail



IPMP application

Monarch IP

Accessories to suit all Monarch IP enclosures

Insulated Mounting Pans

Suitable where use of a metallic pan is not acceptable. Manufactured from black laminated phenolic material and supplied with all fixings, the insulated mounting pan is easy to install and use.

Part Number	Dimensions (mm)			To suit enclosure (mm)	
	Height	Width	Thickness	Height	Width
IPFP0905 [▲]	250	150	6	300	200
IPFP1309 [▲]	350	250	6	400	300
IPFP1313	320	340	6	400	400
IPFP1321 [▲]	320	540	6	400	600
IPFP2113 [▲]	520	340	6	600	400
IPFP2121	520	540	6	600	600
IPFP2129 [▲]	520	740	6	600	800
IPFP2525 [▲]	620	640	6	700	700
IPFP2921	720	540	6	800	600
IPFP2929 [▲]	720	740	6	800	800
IPFP3721 [▲]	920	540	6	1000	600
IPFP3725 [▲]	920	640	8	1000	700
IPFP3729 [▲]	920	740	8	1000	800
IPFP4521 [▲]	1120	540	8	1200	600
IPFP4529 [▲]	1120	740	8	1200	800

[▲] Available on request



IPFP

Double Hinged Insulating Panels

Mainly used for metering applications. They are functional mounting solution for equipment installation that provides full access to the rear of the panel.

Part Number	Dimensions (mm)			To suit enclosure (mm)	
	Height	Width	Thickness	Height	Width
IPHP1313	320	325	6	400	400
IPHP1321	320	525	6	400	600
IPHP2113	520	325	6	600	400
IPHP2121	520	525	6	600	600
IPHP2129	520	725	6	600	800
IPHP2421	595	525	6	partial height	600
IPHP2429	595	725	6	partial height	800
IPHP2525	620	625	6	700	700
IPHP2921	720	525	6	800	600
IPHP2929	720	725	6	800	800
IPHP3221 [▲]	795	525	6	partial height	600
IPHP3229	795	725	6	partial height	800
IPHP3721	920	525	6	1000	600
IPHP3725 [▲]	920	625	8	1000	700
IPHP3729	920	725	8	1000	800
IPHP4521	1120	525	8	1200	600
IPHP4529	1120	725	8	1200	800

[▲] Available on request



IPHP

Hinged Escutcheons

Used for covering internal controls and accessories. They can be mounted singularly or with two or more fitted into the enclosure. Fitting requires universal rail kit (see page 28).

Part Number	Dimensions (mm)			Required (rail kit)	To suit enclosures (mm)	
	Height	Width	Depth		Height	Width
IPHE1313	325	320	18	IPRK1313	400	400
IPHE1321	325	520	18	IPRK1321	400	600
IPHE1329	325	720	18	IPRK1329	400	800
IPHE1621	400	520	18		400	600
IPHE1629	400	720	18		400	800
IPHE2021	500	520	18		400	600
IPHE2029	500	720	18		400	800
IPHE2113	525	320	18	IPRK2113	600	400
IPHE2121	525	520	18	IPRK2121	600	600
IPHE2129	525	720	18	IPRK2129	600	800
IPHE2421	600	520	18		partial	600
IPHE2429	600	720	18		partial	800
IPHE2525	625	620	18	IPRK2525	700	700
IPHE2921	725	520	18	IPRK2921	800	600
IPHE2929	725	720	18	IPRK2929	800	800
IPHE3221	800	520	18		partial	600
IPHE3229	800	720	18		partial	800
IPHE3721	925	520	18	IPRK3721	1000	600
IPHE3725	925	620	18	IPRK3725	1000	700
IPHE3729	925	720	18	IPRK3729	1000	800
IPHE4021	1000	520	18		1000	600
IPHE4029	1000	520	18		1000	800
IPHE4521	1125	520	18	IPRK4521	1200	600
IPHE4529	1125	720	18	IPRK4529	1200	800
IPHE5321	1325	520	18	IPRK5321	1200	600
IPHE5329	1325	720	18	IPRK5329	1200	800
IPHE6121	1525	520	18	IPRK6121	1600	600
IPHE6129	1525	720	18	IPRK6129	1600	800
IPHE6921	1725	520	18	IPRK6921	1800	600
IPHE6929	1725	720	18	IPRK6929	1800	800
IPHE7721	1925	520	18	IPRK7721	2000	600
IPHE7729	1925	720	18	IPRK7729	2000	800



IPHE



Full height hinged escutcheons are incompatible with door stays

Fixed Escutcheons

Used for covering internal controls and accessories. They form a second tier mounting arrangement, in front of the mounting pan. They can be mounted singularly or with two or more fitted into the enclosure. Fitting requires universal rail kit (see page 28).

Part Number	Dimensions (mm)			Required (rail kit)	To suit enclosures (mm)	
	Height	Width	Depth		Height	Width
IPFE0908	225	200	18		—	—
IPFE0913	225	325	18		—	400
IPFE0916	225	400	18		—	—
IPFE0921	225	525	18		—	600
IPFE0929	225	725	18		—	800
IPFE1208	300	200	18		—	—
IPFE1213	300	325	18		400	400
IPFE1216	300	400	18		400	400
IPFE1221	300	525	18		—	600
IPFE1229	300	725	18		—	800
IPFE1308▲	325	200	18	—	—	—

▲ Available on request

Cont.

Monarch IP

Accessories to suit all Monarch IP enclosures

Fixed Esutcheons Cont.

Part Number	Dimensions (mm)			Required (rail kit)	To suit enclosures (mm)	
	Height	Width	Depth		Height	Width
IPFE1313	325	325	18	IPRK1313	400	400
IPFE1316 [▲]	325	400	18	–	–	–
IPFE1321	325	525	18	IPRK1321	400	600
IPFE1329	325	725	18	–	400	800
IPFE1608	400	200	18	–	–	–
IPFE1613	400	325	18	–	–	400
IPFE1616 [▲]	400	400	18	–	–	–
IPFE1621	400	525	18	–	–	600
IPFE1629	400	725	18	–	–	800
IPFE2008	500	200	18	–	–	–
IPFE2013	500	325	18	–	–	400
IPFE2016	500	400	18	–	–	–
IPFE2021	500	525	18	–	–	600
IPFE2029	500	725	18	–	–	800
IPFE2108	525	200	18	–	600	–
IPFE2113	525	325	18	IPRK2113	600	400
IPFE2116	525	400	18	–	600	–
IPFE2121	525	525	18	IPRK2121	600	600
IPFE2129	525	725	18	IPRK2129	600	800
IPFE2408	600	200	18	–	–	–
IPFE2413	600	325	18	–	–	–
IPFE2416	600	400	18	–	–	–
IPFE2421	600	525	18	–	–	–
IPFE2429	600	725	18	–	–	–
IPFE2525 [▲]	625	625	18	IPRK2525	700	700
IPFE2908	725	200	18	–	800	–
IPFE2913	725	325	18	–	800	400
IPFE2916	725	400	18	–	800	–
IPFE2921	725	525	18	IPRK2921	800	600
IPFE2929	725	725	18	IPRK2929	800	800
IPFE3208	800	200	18	–	–	–
IPFE3213	800	325	18	–	–	–
IPFE3216	800	400	18	–	–	–
IPFE3221	800	525	18	–	–	–
IPFE3229	800	725	18	–	–	–
IPFE3708	925	200	18	–	–	–
IPFE3713	925	325	18	–	–	–
IPFE3716	925	400	18	–	–	–
IPFE3721	925	525	18	IPRK3721	1000	600
IPFE3725 [▲]	925	625	18	IPRK3725	1000	700
IPFE3729	925	725	18	IPRK3729	1000	800
IPFE4008	1000	200	18	–	–	–
IPFE4013	1000	325	18	–	–	400
IPFE4016	1000	400	18	–	–	–
IPFE4021	1000	525	18	–	–	600
IPFE4029	1000	725	18	–	–	800
IPFE4508	1125	200	18	–	–	–
IPFE4513 [▲]	1125	325	18	–	1200	400
IPFE4516 [▲]	1125	400	18	–	–	–
IPFE4521	1124	524	18	IPRK4521	1200	600
IPFE4529	1124	724	18	IPRK4529	1200	800

[▲] Available on request

Monarch IP

Accessories to suit all Monarch IP enclosures



Escutcheon Rails

Used where two escutcheons meet in the enclosures.

Part Number	Description	Height (mm)
IPEJ [▲]	Pack of 10	joining bracket
IPER05	–	525
IPER07	–	725
IPER19	–	1975

[▲] Available on request



IPER

Universal Rail Kits

Used to install both fixed and hinged escutcheons and complete with 4 rails and fixings. A pair of height rails and a pair of width rails are provided in each kit.

Part Number	Rail lengths (mm)		To suit enclosures (mm)	
	Rail Height	Rail Width	Height	Width
IPRK1313	375	325	400	400
IPRK1321	375	525	400	600
IPRK1329	375	725	400	800
IPRK2113	575	325	600	400
IPRK2121	575	525	600	600
IPRK2129	575	725	600	800
IPRK2525 [▲]	675	625	700	700
IPRK2921	775	525	800	600
IPRK2929	775	725	800	800
IPRK3721	975	525	1000	600
IPRK3725	975	625	1000	700
IPRK3729	975	725	1000	800
IPRK4521	1175	525	1200	600
IPRK4529	1175	725	1200	800
IPRK6121	1575	525	1600	600
IPRK6129	1575	725	1600	800
IPRK6921	1775	525	1800	600
IPRK6929	1775	725	1800	800
IPRK7721	1975	525	2000	600
IPRK7729	1975	725	2000	800

[▲] Available on request



IPRK

Door Stays

Ensures door remains open even in windy weather ensuring the safety of people working on the installed equipment.

Part Number	Quantity	To suit enclosure width (mm)
IPDS	1	All enclosures 600mm and wider



IPDS



Full height hinged escutcheons are incompatible with door stays

Monarch IP

Accessories to suit all Monarch IP enclosures


Shelves

White powdercoated shelving comes complete with knockout for cabling and all fittings. Designed for use as segregation panels for switchboard applications mounting fixed equipment.

Part Number	Dimensions (mm)		To suit enclosures (mm)	
	Width	Depth	Width	Depth
IPSH211 [▲]	563	105	600	175
IPSH212	563	160	600	270
IPSH214	563	280	600	400
IPSH215	563	380	600	500
IPSH216	563	480	600	600
IPSH254 [▲]	663	280	700	400
IPSH292 [▲]	763	160	800	270
IPSH294	763	280	800	400
IPSH295	763	380	800	500
IPSH296	763	480	800	600

[▲] Available on request

STATIC
UDL
200kg



IPSH




These shelves are NOT designed for load during transport.

DIN Rails

Used for mounting DIN switchgear and accessories into the enclosure. It is available for all models in aluminium, steel and slotted designs.

Part Number	Material	Description	Dimensions (mm)	
			Length	Depth
IPDN03	Aluminium	–	360	15
IPDN05 [▲]			560	15
IPDN07 [▲]			760	15
DIN35/7.5	Steel	–	2000	7.5
DIN35/7.5SL	Steel slotted	–	2000	7.5
DIN35/15AL15	Aluminium	–	1500	15
DINSB	–	Mounting kit, angle support brackets	–	–

[▲] Available on request



DIN35/7.5SL

Eye Bolts

Ensures enclosure is not damaged when lifted and can be moved safely. Compliant to AS4991: Lifting Devices.

Part Number	Quantity	Lift Rating	To suit enclosure width (mm)
LEB/12	2	125kg per bolt	all




LEB/12

Mounting Brackets

For ease of installation and fixing to the mounting surface. Mounting brackets ensure optimum installation and safety.

Part Number	Material	Quantity	To suit enclosure width (mm)
MEB/S	Stainless steel	4	all
IPWM	Zinc coated steel	4	all
IPWM/A	Aluminium	4	all
IPWM/S	Stainless steel	4	all



MEB/S

Monarch IP

Accessories to suit all Monarch IP enclosures



Standard Rails – C Section

Used to fit additional accessories and rails in the enclosure.

Part Number	Description	Height (mm)	To suit enclosure depth (mm)
IPCR01 [▲]		137	–
IPCR02		232	270
IPCR03		360	400
IPCR04		460	500
IPCR05		560	600
IPCR07		760	800
IPCR12	For loose supply (customer cut to length)	1200	–
IPTO	Takeoff bracket (pack of 10)	–	–



IPCR



IPTO


[▲] Available on request

Universal Rails

Designed for mounting equipment inside an enclosure. Either fixed lengths or can be cut to size requirements.

Part Number	Description	Length (mm)	To suit enclosure height (mm)
IPUV	25 pitch	1975	all
UV1 [▲]	20 pitch	1984	all

[▲] Available on request




IPUV

19" Mounting Rails

Designed for mounting equipment inside an enclosure. Either fixed lengths or can be cut to size requirements.

Part Number	Dimensions (mm)			To suit enclosures (mm)	
	Height	Width	Depth	Height	Width
UV19	1946	58.5	76	–	
IPRU11	536	–	–	600	
IPRU15	758	–	–	800	
IPRU24	1158	–	–	1200	600
IPRU32 [▲]	1469	–	–	1600	
IPRU38 [▲]	1736	–	–	1800	
IPRU42 [▲]	1958	–	–	2000	
IPRU11/800 [▲]	536	–	–	600	
IPRU15/800 [▲]	758	–	–	800	
IPRU24/800 [▲]	1158	–	–	1200	800
IPRU32/800 [▲]	1469	–	–	1600	
IPRU38/800 [▲]	1736	–	–	1800	
IPRU42/800 [▲]	1958	–	–	2000	

[▲] Available on request



IPRU

Monarch IP

Accessories to suit all Monarch IP enclosures

Laptop Lecterns

Designed to allow fast and easy access when using a laptop computer. The laptop lectern protrudes 45mm inside the door. Mounting requires door rails (purchased separately).

Part Number	Description	Dimensions (mm)		To suit door (mm)	
		Width	Depth	Height	Width
IPLL▲	Laptop lectern	440	300	600 & above	600 & above
IPRD6▲	Door rails (set of 2)	—	—	—	600
IPRD8▲		—	—	—	800

▲ Available on request




IPLL

Document Holders

Designed to standard A4 documents such as procedures and diagrams to ensure that they are kept clean and conveniently located.

Part Number	Description	To suit enclosure width (mm)
IPPLN	A4 Plastic	all
IPPLN04/35	A4 Metal	400 & above
IPPLN04/80▲	A4 Metal – Folder	400 & above
IPPLN06/15	A3	600 & above
IPPLN06/35▲	A3 Metal	600 & above
IPPLN06/80▲	A3 Metal – Folder	600 & above

▲ Available on request.



IPPLN

Schedule Holders

Used to ensure maintenance schedules are always displayed prominently.

Part Number	Description	Mounting	Colour	Dimensions (mm)			To suit enclosure (mm)	
				Height	Width	Depth	Height	Width
IPLC150▲	150 line	Door rail	Pebble Grey RAL7032	255	210	—	400	300
IPLC40▲	40 line			230	110	—	300	200
LCH40	40 line	Tape or rivets	Light Grey RAL7035	230	110	8	300	200
LCH60	60 line			260	210	8	400	300
LCH78▲	78 line			380	110	8	500	200

▲ Available on request




IPLC

Backmount Frame

Part Number	Description	Height (RU)
FCCD15/19*▲	15-Way, 19 inch	3

▲ Available on request

* 19 inch mounting rails required refer to page 88.



FCCD15/19

Load Centre

Part Number	Description	Height (RU)
FCLC19/19*	19-pole, 19 inch	5

* 19 inch mounting rails required refer to page 88.



FCLC19/19

Monarch IP

Accessories to suit all Monarch IP enclosures



General Accessories

A range of general accessories to suit all Monarch IP enclosures.

Part Number	Product	Description
IPNLK [▲]	Night latch kit bracket	To enable Lockwood deadbolt to be fitted
IPP06 [▲]		M6
IPP10 [▲]	Hole plug (pack of 20)	M10
IPP13 [▲]		M13
IPBO612		M6 x 12mm
IPBO625		M6 x 25mm
IPBO812	Bolt – hex head (pack of 20)	M8 x 12mm
IPBO825		M8 x25mm
IPBO830 [▲]		M8 x 30mm
IPBO840/D [▲]	Accessory kit seal screw (pack of 10)	M8 x 40
IPN06 [▲]	Hex head nuts (pack of 20)	M6
IPN08 [▲]		M8
IPCG06	Cage Nuts (pack of 20)	M6
IPCG08		M8
IPCN06	Foam back nuts (pack of 20)	M6
IPCN08		M8
IPTO616 [▲]	Screws – taptite (pack of 20)	M6 x 16mm
IPTPO616/S [▲]	Tamper proof screws with security bit	M6 x 16mm (pack of 10)
IPWF06 [▲]	Flat washers (pack of 20)	M6
IPWF08 [▲]		M8
IPWG06	Seal washers (pack of 20)	Small
IPWS06 [▲]	Star washers (pack of 20)	M6
IPWS08		M8
IPWSP06	Spring washers (pack of 20)	M6
IPWSP08		M8
IPOR06 [▲]	Sealing ring (pack of 20)	M6
IPCDH [▲]	D handle	Chrome
ECESK [▲]	Earth strap kit	–
IPZRLG [▲]	Z Rail	760mm
TUP/P20	Touch Up Paint (300g)	Pebble Grey RAL7032
TUP/P29		Light Grey RAL7035

[▲] Available on request

Locks

Locks to suit Monarch IP enclosures

Standard Locks

Enclosure	Zinc Coated Steel	Stainless Steel	Aluminium
≤1600mm	IP020 – chromed steel lock with 7mm square steel insert	IP020/S – black powdercoated lock with 7mm square stainless steel insert	IP020/PS – chromed steel lock with 7mm square steel insert
+1600mm	IP050 – lockable L handle keyed 92268	IP050 – lockable L handle keyed 92268	IP050 – lockable L handle keyed 92268

Lock Options for Monarch IP Enclosures

There are a number of lock options available that are suitable for use on Monarch IP enclosures. Contact your local sales representative to discuss your requirements.

Product	Description	Part Number	Standard Lock/Insert	Alternative insert	Keys	
					Lockable handles	Zinc, 4-way
Turnbuckle	chromed steel	IP020	7mm square – steel	See below		SKZ
	powdercoated	IP020/PS	7mm square – stainless steel	See below		SKZ
	stainless steel	IP020/S	7mm square – stainless steel	See below		SKZ
		IP028S/S	8mm square slotted – stainless steel	See below		
Wing knob	lockable	IP030	Key code 92268		SK3	
	lockable	IP030/CL001	Key code CL001			
	lockable	IP030/L003	Key code L003			
	padlockable	IP032	Suit 8mm hasp			
	padlockable - stainless steel	IP032/S	Suit 8mm hasp			
	non-lockable	IP111	–			
T-handle	lockable	IP040	Key code 92268		SK3	
L-handle	lockable	IP050	Key code 92268		SK3	
	lockable – stainless steel	IP050/S	Key code 92268		SK3	
	padlockable – steel	IP052	–			
	padlockable – stainless steel	IP052/S	–			
Swing handle	padlockable – steel	IP060	Suitable for up to 9mm diameter pad-lock shackle.			
	padlockable – stainless steel	IP060/S				



Lock Inserts for IP020 Locks

The IP020 locks are available with an option lock insert for use on all Monarch IP enclosures. Contact your local sales engineer to discuss your requirements.

To suit lock style	Description	To suit lock	Standard Insert	3mm double bit pin		8mm square		8mm square slotted		8mm triangle	
				Steel	Stainless Steel	Steel	Stainless Steel	Stainless Steel	Steel	Stainless Steel	Stainless Steel
Turnbuckle	chromed steel	IP020	7mm square – steel	LKINS3P		LKINS8S		LKINS8SS/S		LKINS8T	
	powdercoated with SS insert	IP020/PS	7mm square – stainless steel		LKINS3P/S		LKINS8S/S	LKINS8SS/S		LKINS8T/S	
	stainless steel	IP020/S	7mm square – stainless steel		LKINS3P/S		LKINS8S/S	LKINS8SS/S		LKINS8T/S	
Key required – zinc			SKZ	SKZ	SKZ	SKZ	SKZ	SKZ	SKZ	SKZ	SKZ

Our LED lighting solutions provide light inside an enclosure when visibility is required for both safety and efficacy.



Compact, high-output LED lighting designed to enhance visibility within enclosures and rack systems. Up to four light units can be daisy chained from a single power supply, with linking capability of up to 36W per run. Lights can be mounted directly to 19" rack rails, with optional mounting kits available for enclosures without rack rails.

When roof-mounted, the slim-profile design allows unobstructed operation of full-height swing frames and hinged escutcheons. An optional PIR motion sensor provides automatic switching for improved energy efficiency.

B&R's LED lighting solutions are applied to provide excess light within an enclosure and becomes a continuous light source to provide extra visibility.

- Energy saving up to 50% compared with traditional fluorescents under the same lux.
- Life span – over 50,000 hours
- Colour temperature: warm white.
- Available in 12V and 24V options.
- Easy linking up to 36 watts per run.
- Easy to install.
- Low voltage — safe and efficient.
- Manufactured from aluminium with black plastic end caps and acrylic lens.
- Light source – SM3528 LED
- Operating temperature – -20°C to 40°C indoors



This information is provided as a guide only. Contact your local sales representative to discuss your requirements.

Technical Operating Data

Length (mm)	Voltage (DC)	Power (W)	Radiance	Colour Temp	Luminous Flux (lm)*	LED Current (A)
300	12/24	3	90°	4400	280/360	0.18
500	12/24	5	90°	4400	460/600	0.18

Monarch IP

Part Number	Power (V)	Inclusions					Required Mounting Bracket			To suit enclosure	
		LED Light	Power Supply	Splitter	Switch	Connectors	IPLKB04	IPLKB06	IPLKB08	Width (mm)	Optional
BRLED300	12	•	•		•		•			400	BRMOT PIR Motion Sensor
BRLED300/24	24	•	•		•		•			400	
BRLED500	12	•	•		•			•	•	600 or 800	
BRLED500/24	24	•	•		•			•	•	600 or 800	
BRLEDK03	–	•		•		•	•			400	
BRLEDK05	–	•		•		•		•	•	600 or 800mm	