


NOX12


Wall-mount air conditioners
for outdoor applications




1250W

COOLING CAPACITY

DIMENSIONS (mm)



PERFORMANCE



P = Cooling capacity (W)

Ta = Ambient Temperature (°C)

Ti = Internal cabinet temperature (°C)

TECHNICAL SPECIFICATIONS

FEATURES	UoM	NOX12B0E1C0000	NOX12K0E1C0000
Cooling capacity EN14511 - A35A35	W	1250	1250
Cooling capacity EN14511 - A35A50	W	930	930
Power supply	V ~ Hz	230 - 1 - 50/60	400/460 - 2 - 50/60
Width - Height - Depth	mm	400 - 1000 - 250	400 - 1000 - 250
Max current	A	3.2	1.8
Inrush current	A	17.1	9.8
T Fuse	A	6	4
Power draw EN14511 - A35A35	W	590	590
Power draw EN14511 - A35A50	W	680	680
Electrical connection	-	4-pin plug	4-pin plug
Cabinet air fan capacity	m³/h	540	540
Internal temperature range	°C	20 - 45	20 - 45
Temperature regulation	-	Electronic thermostat TX-i40 factory set to 35°C, with 3m cable and DIN rail installation kit	
External temperature range	°C	-20 – +55	-20 – +55
Ingress protection - cabinet side	-	IP55	IP55
Noise level	dB (A)	65	65
Weight	kg	39	41
Conformity	-	ENI CE UK CA	ENI CE UK CA

* Type 4X only in stainless steel framework version