

CT Metering

Small main boards & CT chassis systems



- Suitable for the mounting of supply authority and private current transformers.
- Manufactured from 1.6mm zinc coated steel or 316 stainless steel available on request.
- Powdercoated Pebble Grey RAL7032.



ORDERING GUIDE

Part Number	Description	CT Chassis Rating	Test	Dimensions (mm)		
				Height	Width	Depth
SMB ENCLOSURES IP66						
SMB1/1	Cabinet supplied with meter and consumer panel (NT, SA, NSW, TAS)	600A	50kA for 1 sec	2000	800	500
SMB1/15	Cabinet supplied with meter and consumer panel (ex VIC)	630A	36kA for 1 sec	2075	800	500
SMB1/15/S	Cabinet supplied with meter and consumer panel (ex VIC)	630A	36kA for 1 sec	2075	800	500
SMB1/40	Cabinet supplied with meter and consumer panel (QLD only)	600A	50kA for 1 sec	2000	800	400
CT ENCLOSURES IP33						
CTB/E2	Cubicle empty fitted with 3 x 32A HRC potential fuses (holders only), weatherproof. To suit CTC200/400A and CTC/630A. Available in RAL7035 Light Grey.			500	720	340
CT CHASSIS						
CTC/68	CT chassis with busbar	600A	50kA for 1 sec	550	770	100
CTC200/400A	CT chassis for S-Type CTs	200/400A	25kA for 1 sec	500	400	95
CTC630A	CT chassis for T-Type CTs	630A	36kA for 1 sec	500	400	120

ACCESSORIES

Part Number	Product	Description	CTB/E2
CTBSHLD	Shield	Safety screen for CTB/E2	•
CTPFK	Potential fuse kit	Current transformer – no fuse links	•



CTBSHLD



CTPFK



CTB/E2