

# PRODUCT SPOTLIGHT



HAZARDOUS AREAS

## Emergency & Non-Emergency Fluorescent Zones 1 & 2, 21 & 22



### OVERVIEW

- Suitable for use in chemical, petrochemical, dust, grain, and other hazardous areas.
- EOL (end of life) on ballast.
- Central mechanical interlocking devices for safe cover removal.
- Lamp options – twin 14W, 18W, 28W and 36W
- Lamp holder – T5 for 14W & 28W, T8 for 18W & 36W

Comes standard with:

- 2 x lamps
- EOL on ballast
- Dust cover on key locks
- Internal brass plate



PROTECTION RATINGS	CERTIFICATION	AMBIENT TEMPERATURE	RATED VOLTAGE	RANGE
Ex deq IIC T4 Gb / Ex tD A21 T80°C Ex deq mb IIC T4 Gb / Ex tD A21 T80°C (emergency)	IECEX CQM 10.0012	-20°C ~ +40°C	AC 110-240V, 50/60Hz	CZ0866/2 Series CZ0865/2 Series

### ORDERING GUIDE

Dimensions (mm)

Catalogue No.	Type	Watts	No. of Lamps	Length	Width	Height	Fixings	Lamp Holder	Weight (kg)
FLUG014X2C	Non-emergency	14	2	725	222	145	400	T5	5.0
FLUG018X2C		18	2	725	222	145	400	T8	5.0
FLUG028X2C		28	2	1335	222	145	800	T5	7.9
FLUG036X2C		36	2	1335	222	145	800	T8	7.9
FLUG014X2CE <sup>▲</sup>	Emergency	14	2	725	222	145	400	T5	6.8
FLUG018X2CE		18	2	725	222	145	400	T8	6.8
FLUG028X2CE <sup>▲</sup>		28	2	1335	222	145	800	T5	9.9
FLUG036X2CE		36	2	1335	222	145	800	T8	9.9

<sup>▲</sup> Available on request

