

Infinity 3G

Standard Designs - Queensland

A modular switchboard for multi-residential and commercial applications.

- Robust construction to ensure long service life.
- Wide double door enclosures have no central mullion allowing full width accessibility.
- Swing handle comes with 45mm cylinder keyed to 92268.
- Manufactured from 1.6mm thick zinc coated steel.
- Powdercoated Light Grey RAL7035.

Comes standard with:

- Large 3mm aluminium gland plate
- Stainless steel door hinges
- Recessed swing handle lock (keyed to 92268)
- Document holder
- 3-point locking



ORDERING GUIDE

METALWARE ASSEMBLED

No functional devices, wiring or labels included.

Part Number	External Dimensions (mm)			Main Switch Section	Available Metering Configuration	Sub Main Section	Mounting
	Height	Width	Depth				
TGXQ10M1P	1270	1070	450	Space for Schneider MCCB Max 250A	10 x single phase 6 x 3 phase 7 x dual tariff with 3 x network devices	24 Pole DIN (no devices)	Wall
TGXQCT250	2170	670	450	Space for Schneider MCCB Max 250A	1 x CT tenant	Space for 2 x Schneider MCCB Max 250A	Plinth
TGXQCT630	2170	1070	450	Space for Schneider MCCB Max 630A	1 x CT tenant	Space for 1 x Schneider MCCB Max 630A	Plinth

ASSEMBLED AND WIRED

Part Number	External Dimensions (mm)			Main Switch Section	Available Metering Configuration	Sub Main Section	Mounting
	Height	Width	Depth				
TGXQ10M1P/CW	1270	1070	450	Supplied with Schneider 250A MCCB LV431140	Wired for 10 x single phase	Supplied with 10 x 63A 1P MCB's A9F44163	Wall
TGXQCT250/CW	2170	670	450	Supplied with Schneider 250A MCCB LV431140	1 x CT tenant	250A rated tails (no devices)	Plinth



TGXQ10M1P
TGXQ10M1P/CW



TGXQCT250
TGXQCT250/CW



TGXQCT630

